

SMOKE PROTECTIVE CLOSURES

SMOKESHIELD® ELEVATOR

CLOPAY COMMERCIAL – MODEL CERF10



Model CERF10 Door

THE MOST DESIGN FORWARD HOISTWAY SMOKE ENCLOSURE AVAILABLE

LIMITLESS DESIGN FREEDOM

We've applied nearly 100 years of experience in life safety and fire protection to help innovate SmokeShield® Elevator enclosure. This hoistway closure makes it possible to eliminate the IBC elevator lobby requirement and allows the design visionary to pursue more spacious and unique layouts in areas typically requiring elevator lobbies.

SAFETY

SmokeShield® Elevator's patented GuideLock™ technology positively re-seals the hoistway after cycling, while the transparency and graphic designs of the curtain itself are both instructional and intuitive for the user in an emergency situation. This resealing is important, because if re-sealing does not occur, smoke will migrate and create preventable damage.

clopaycommercial.com

AESTHETICS

SmokeShield® Elevator is the most design-adaptable hoistway smoke enclosure in the industry. SmokeShield® Elevator's design versatility is evident in masonry, drywall or other fascia materials, offering the broadest range of mounting possibilities. Any exposed guides or bottom bars can be finished to match, complement or contrast their surroundings with custom powder coating or our proprietary #4 brushed stainless matching guide anodized option.

SECURITY

SmokeShield® Elevator's headroom, backroom and sideroom requirements are some of the smallest on the market. Additionally, the control box and battery backup are invisibly located within the headbox.

SMOKESHIELD ELEVATOR KEY FEATURES:

ADDITIONAL AVAILABLE SPACE

SmokeShield® Elevator fits into less than 10" of headroom for hoistway openings up to 12' height and 12' wide

1. NO VISIBLE FASTENERS

Our unique guide components seamlessly fit together

**2. CURTAIN RESEALS ELEVATOR**

Every time after cycling as a result of our patented GuideLock™ technology



Complies with:

- IBC 2003 – PRESENT
- ICC-ES Report AC – 77

Listed:

- UL 1784
- UL 325
- UL 864
- ASTM E84
- California State Fire Marshal

**ADDED CONVENIENCE**

A time delay prevents activation during brief power outages

3. EASY WIRING CONNECTIONS

115V line connection and 24V alarm connection with accessible buttons for alarm and battery connections

**4. INTUITIVE GRAPHICS**

For evacuees and emergency responders to ensure simple operation

5. SUPERIOR VISIBILITY

The curtain's transparent material provides an increased safety margin for firefighters and EMTs

6. INTUITIVE OPERATION

Optimally positioned open switch is factory mounted to both sides

7. BACK-UP

ADA compliant lift strap

OPERATION AND MOUNTING REQUIREMENTS

SmokeShield® Elevator deploys upon notification by the fire alarm control panel or local smoke detectors and is re-opened by pushing the curtain-mounted switch or, in the event of complete power loss, by simply lifting the emergency lift strap located at the bottom of the curtain. Patented GuideLock™ technology ensures a complete hoistway perimeter seal after every cycle.

SmokeShield Elevator automatically resets and auto-opens after the alarm is cleared.

Interior mount only.

STANDARD

- **Battery Backup:** Capable of holding door open for up to 10 hours and operating the door for up to 4 hours after power failure

OPTIONAL

- **Wire Directly:** For enhanced reliability, wire to building back-up power source
- **Finishes:** Standard RAL and custom powder coat finishes and anodized guide finish to match #4 brushed stainless steel

CUSTOM-DESIGNED SOLUTIONS

Contact our experienced Architectural Design Support Team for help in customizing our products to fit your specific application at www.architectdoorhelp.com.



For more information on these and other Clopay products, visit clopaycommercial.com. Architects and specifiers, visit architectdoorhelp.com.



©2026 Clopay Corporation. All rights reserved.

CMDC-SMOKESHIELDED-23_REV0926